


Service Manual Trucks

Group **37**

Electrical Schematic:
Fog and Driving Lamps


VNL, VNM

From Build Date 2.98






CONNECTOR AND SPLICE INFORMATION CONNECTORS VIEWED FROM CABLE ENTRY




CONNECTOR 1
AUX LAMP ENABLE RELAY R1

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
30	34	12 VOLT SUPPLY
86	140A	DIMMER CONTROL
87	34A	SUPPLY LAMP SWITCH
85	OR-F/OR-H	GROUND




CONNECTOR 2
CHASSIS HARNESS PASS THROUGH

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
B7	37	DRIVING LP SUPPLY
B9	35	FOG LAMP SUPPLY




CONNECTOR 3
SWITCH AUXILIARY LAMPS

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
B	39A	LED SUPPLY
I	39/39A	TO CHANGE OVER RELAY
3	34A	12 VOLT SUPPLY
9	0J-G	GROUND
10	141-D	SWITCH ILLUMINATION




CONNECTOR 4
DRIVING LAMP RIGHT SIDE

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
A	37	12 VOLT SUPPLY
B	0M	GROUND




CONNECTOR 5
DRIVING/FOG LAMP LEFT SIDE

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
A	35L	12 VOLT SUPPLY
B	37L	12 VOLT SUPPLY
C	0M	GROUND




CONNECTOR 6
FOG LAMP LEFT SIDE

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
A	35	12 VOLT SUPPLY
B	0M	GROUND




CONNECTOR 7
DRIVING LAMP LEFT SIDE

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
A	37	12 VOLT SUPPLY
B	0M	GROUND




CONNECTOR 8
AUX LAMP CHANGE OVER RELAY R5

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
30	39	12 VOLT SUPPLY
86	38	DIMMER CONTROL
87	37	12 VOLT SUPPLY
85	OR-J	GROUND
87A	35	12 VOLT SUPPLY




CONNECTOR 9
DRIVING/FOG LAMP RIGHT SIDE

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
A	35R	12 VOLT SUPPLY
B	37R	12 VOLT SUPPLY
C	0M	GROUND



CONNECTOR 10
FOG LAMP RIGHT SIDE


TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
A	35	12 VOLT SUPPLY
B	0M	GROUND



CONNECTOR 11
SPLICE PACK OG

TABLE OF CONTENTS		
CAVITY	CIRCUIT	FUNCTION
A	OG	GROUND
F	0J-G	AUX LAMP SW


SPLICE PACK OG




SPLICE SF3 VEHICLE LOCATION: CHASSIS HARNESS
1250MM FWD OF PASS-THROUGH BREAKOUT




SPLICE SF1 VEHICLE LOCATION: CHASSIS HARNESS
1150MM FROM PASS THROUGH BREAKOUT



SPLICE SF2 VEHICLE LOCATION: CHASSIS HARNESS
1200MM FROM PASS THROUGH BREAKOUT




SPLICE OM-2 VEHICLE LOCATION: LH FOG & DRIVING
LAMP JUMPER



SPLICE OM-1 VEHICLE LOCATION: RH FOG & DRIVING
LAMP JUMPER

SYMBOL DEFINITION



CHANGE HISTORY	
DESCRIPTION	

